

Introduction

`fbmgr` is used to start and stop your Firebird [Superserver](#). This is different from starting and stopping a [database](#) - as explained in the [gfix](#) manual - as the running databases rely on the Firebird service/daemon. This daemon is the Firebird *engine* - without it, nothing will run under Superserver.

Note: If you are using Firebird [Classic](#), this chapter does not apply and it is entirely possible that the executables mentioned in this chapter may not even exist in your installation directory.

Note: If you are using Firebird 2.5 onwards, you will see a message whenever you use `fbmgr`, telling you that `fbmgr` has been deprecated. From Firebird 3.0 onwards, this utility will no longer be present in the Firebird releases. You are advised to use the `fbguard` utility instead. See the [chapter on fbguard](#) for details.

On Windows systems, the engine runs as a service and is slightly different. Windows will be discussed separately in this manual for that reason.

In the remainder of this manual, we will discuss the following:

- Differences between Windows and Linux systems.
- Command-line options for `fbmgr`.
- `fbmgr` commands and their parameters.
- Running `fbmgr` in interactive or batch modes.
- Some caveats, gotchas and foibles of `fbmgr`.

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
<http://ibexpert.com/docu/doku.php?id=01-documentation:01-08-firebird-documentation:firebird-superserver-manager:introduction>

Last update: **2023/07/11 16:13**

