

# File Functions

The following file-handling functions are available in IBEBlock:

Function	Description
<a href="#">ibec_DeleteFile</a>	Erases the file from the disk.
<a href="#">ibec_DirectoryExists</a>	Call ibec_DirectoryExists to determine whether the directory specified by the Name parameter exists.
<a href="#">ibec_SetCurrentDir</a>	
<a href="#">ibec_RemoveDirectory</a>	Removes a directory.
<a href="#">ibec_FileExists</a>	Tests if a specified file exists.
<a href="#">ibec_FileSize</a>	Returns the size of the specified file.
<a href="#">ibec_GetFiles</a>	Retrieves specified file or list of files.
<a href="#">ibec_LoadFromFile</a>	Loads file data into variable.
<a href="#">ibec_SaveToFile</a>	Saves value of variable into file.
<a href="#">ibec_CopyFile</a>	Copies an existing file to a new one.
<a href="#">ibec_MoveFile</a>	Renames an existing file or a directory (including all its children).
<a href="#">ibec_FileDateTime</a>	Returns the TIMESTAMP of a specified file.
<a href="#">ibec_SetFileDateTime</a>	
<a href="#">ibec_GetCurrentDir</a>	Returns the fully qualified name of the current directory.
<a href="#">ibec_GetRunDir</a>	Returns the path of the currently executing program (IBExpert.exe or IBEScript.exe).
<a href="#">ibec_ExtractFileDir</a>	Extracts the drive and directory parts from FileName.
<a href="#">ibec_ExtractFileName</a>	Extracts the name and extension parts of a file name.
<a href="#">ibec_FileAttr</a>	
<a href="#">ibec_SetFileAttr</a>	
<a href="#">ibec_RenameFile</a>	
<a href="#">ibec_ForceDirectories</a>	Creates all the directories along a directory path if they do not already exist.

The following functions are intended for working with files in stream mode:

Function	Description
<a href="#">ibec_fs_CloseFile</a>	Closes the file opened with the ibec_fs_OpenFile function.
<a href="#">ibec_fs_Eof</a>	Closes the file opened with the ibec_fs_OpenFile function.
<a href="#">ibec_fs_OpenFile</a>	Opens a file for reading or writing.
<a href="#">ibec_fs_Position</a>	Returns the current offset into the stream for reading and writing.
<a href="#">ibec_fs_Readln</a>	Reads a line of text from a file.
<a href="#">ibec_fs_ReadString</a>	Reads count bytes from the file stream.
<a href="#">ibec_fs_Seek</a>	Resets the current position of the file stream.
<a href="#">ibec_fs_Size</a>	Returns the length, in bytes, of the file stream.
<a href="#">ibec_fs_SetSize</a>	
<a href="#">ibec_fs_Writeln</a>	
<a href="#">ibec_fs_WriteString</a>	Writes a srtring onto the file stream stream.
<a href="#">ibec_fs_ReadByte</a>	Reads one byte from the file stream and returns an unsigned integer value (0..255).
<a href="#">ibec_fs_WriteByte</a>	Writes one byte to the file stream as a 8-bit unsigned integer.

Function	Description
<a href="#">ibec_fs_ReadWord</a>	Reads two bytes from the file stream and returns an unsigned integer value (0..65535).
<a href="#">ibec_fs_WriteWord</a>	Writes two bytes to the file stream as a 16-bit unsigned integer.
<a href="#">ibec_fs_ReadDoubleWord</a>	Reads four bytes from the file stream and returns an unsigned integer value (0..4294967295).
<a href="#">ibec_fs_WriteDoubleWord</a>	Writes four bytes to the file stream as a 32-bit unsigned integer.
<a href="#">ibec_fs.ReadInt32</a>	Reads four bytes from the file stream and returns a signed integer value (-2147483648..2147483647).
<a href="#">ibec_fs_WriteInt32</a>	Writes four bytes to the file stream as a 32-bit signed integer.

The following functions were introduced to handle work with INI files:

Function	Description
<a href="#">ibec_ini_Open</a>	Erases all data from the INI file in the memory.
<a href="#">ibec_ini_Close</a>	Frees the memory associated with the INI file object.
<a href="#">ibec_ini_ReadString</a>	Erases an entire section of an INI file.
<a href="#">ibec_ini_WriteString</a>	Saves the contents of the INI file to a variable.
<a href="#">ibec_ini_Clear</a>	Instantiates an INI file object.
<a href="#">ibec_ini_EraseSection</a>	Retrieves a string value from an INI file.
<a href="#">ibec_ini_UpdateFile</a>	Sets the contents of the INI file from a variable.
<a href="#">ibec_ini_SetStrings</a>	Flushes buffered INI file data to disk.
<a href="#">ibec_ini_GetStrings</a>	Writes a string value to an INI file.

Please note that all ibec\_ini\_xxx functions, except ibec\_ini\_ReadString and ibec\_ini\_Open, return NULL.

From:  
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:  
<http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-03-file-functions>

Last update: **2023/07/05 17:37**

