

# ibec\_CopyFile

Copies an existing file to a new file.

## Description

The `ibec_CopyFile` function copies an existing file to a new file. If the `FailIfExists` parameter is `@True` and the new file already exists, the function fails. If this parameter is `False` and the new file already exists, the function overwrites the existing file.

This function supports Unicode (UTF8) file names. You can still use ANSI names, necessary checks and conversion are performed automatically.

## Syntax

```
function ibec_CopyFile(ExistingFileName, NewFileName : string;  
                      FailIfExists : Boolean) : Boolean;
```

## Example

```
execute IBEBlock  
returns (cout varchar(100))  
as  
begin  
    if (ibec_CopyFile('d:\txt.csv', 'd:\txtcopy.csv', false)) then  
        cout = 'Operation completed!';  
    else  
        cout = 'Operation NOT completed!';  
    suspend;  
end
```

From:  
<http://ibexpert.com/docu/> - IBExpert

Permanent link:  
[http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-03-file-functions:ibec\\_copyfile](http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-03-file-functions:ibec_copyfile)

Last update: 2023/04/28 02:48

