ibec_SetFileAttr

ibec_SetFileAttr sets the file attributes of the file specified by FileName to the value given by Attr.

Description

The value of Attr is formed by combining the appropriate file attribute constants:

```
Constant     Value     Description
-----------------------------------------------
__faReadOnly $00000001 Read-only files
__faHidden   $00000002 Hidden files
__faSysFile  $00000004 System files
__faVolumeID $00000008 Volume ID files
__faDirectory$00000010 Directory files
__faArchive  $00000020 Archive files
__faAnyFile  $0000003F Any file
```

ibec_SetFileAttr returns zero if the function was successful. Otherwise the return value is a Windows error code.

This function now supports Unicode (UTF8) file names. You can still use ANSI names; necessary checks and conversion are performed automatically.

Syntax

```
  function ibec_SetFileAttr(FileName : string; Attr : integer) : integer;
```

Example

```
FileAttr = ibec_FileAttr(TargetFileName);
if (ibec_and(OldFileAttr, __faReadOnly) = __faReadOnly) then
  ibec_SetFileAttr(TargetFileName, ibec_xor(OldFileAttr,
__faReadOnly));
```

From:
http://ibexpert.com/docu/ - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-03-file-functions:ibec_setfileattr

Last update: **2023/05/02 15:38**