

ibec_SetFileAttr

ibec_SetFileAttr sets the file attributes of the file specified by FileName to the value given by Attr.

Description

The value of Attr is formed by combining the appropriate file attribute constants:

Constant	Value	Description
__faReadOnly	\$00000001	Read-only files
__faHidden	\$00000002	Hidden files
__faSysFile	\$00000004	System files
__faVolumeID	\$00000008	Volume ID files
__faDirectory	\$00000010	Directory files
__faArchive	\$00000020	Archive files
__faAnyFile	\$0000003F	Any file

ibec_SetFileAttr returns zero if the function was successful. Otherwise the return value is a Windows error code.

This function now supports Unicode (UTF8) file names. You can still use ANSI names; necessary checks and conversion are performed automatically.

Syntax

```
function ibec_SetFileAttr(FileName : string; Attr : integer) : integer;
```

Example

```
FileAttr = ibec_FileAttr(TargetFileName);  
if (ibec_and(OldFileAttr, __faReadOnly) = __faReadOnly) then  
  ibec_SetFileAttr(TargetFileName, ibec_xor(OldFileAttr,  
  __faReadOnly));
```

From:

<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:

http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-03-file-functions:ibec_setfileattr

Last update: **2023/05/02 15:38**

