

ibec_RecompileProcedure

Recompiles [stored procedures](#).

Description

This function recompiles (alters using current procedure source) a specified [stored procedure](#) and returns an empty string if no error occurs or an error message otherwise. Instead of a procedure name you can specify an empty string to recompile ALL database stored procedures.

Syntax

```
function ibec_RecompileProcedure(Connection : variant; ProcedureName : string) : string;
```

Example of usage

1. Recompile a single stored procedure using the current connection:

```
execute ibeblock
returns (ErrorMessage varchar(1000))
as
begin
    db = ibec_GetDefaultConnection();
    ErrorMessage = ibec_RecompileProcedure(db, 'MY_PROC');
    if (ErrorMessage <> '') then
        suspend;
end
```

2. Recompile ALL database procedures using the current connection:

```
execute ibeblock
returns (ErrorMessage varchar(10000))
as
begin
    ErrorMessage = ibec_RecompileProcedure(0, '');
    if (ErrorMessage <> '') then
        suspend;
end
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-06-database-functions:ibec_recompileprocedure

Last update: **2023/07/06 03:42**

