

ibec_RecompileTrigger

Recompiles [triggers](#).

Description

This function recompiles (alters using current trigger source) a specified [trigger](#) and returns an empty [string](#) if no error occurs or an error message otherwise. Instead of a trigger name you can specify an empty string to recompile ALL database triggers.

Syntax

```
function ibec_RecompileTrigger(Connection : variant; TriggerName : string)
: string;
```

Examples of usage

1. Recompile a single trigger using the current connection:

```
execute ibeblock
returns (ErrMsg varchar(1000))
as
begin
    db = ibec_GetDefaultConnection();
    ErrMessage = ibec_RecompileTrigger(db, 'MYTABLE_TRG_BI');
    if (ErrMsg <> '') then
        suspend;
end
```

2. Recompile ALL database triggers using the current connection:

```
execute ibeblock
returns (ErrMsg varchar(10000))
as
begin
    ErrMessage = ibec_RecompileTrigger(0, '');
    if (ErrMsg <> '') then
        suspend;
end
```

From:
<https://ibexpert.com/docu/> - **IBExpert**

Permanent link:
https://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-06-database-functions:ibec_recompiletrigger

Last update: **2023/07/06 03:47**

