ibec_GetGlobalVar

ibec_GetGlobalVar returns the value of a specified global Local variables / DECLARE VARIABLE statement|variable. If the variable does not exist, this function returns the value passed in DefaultValue.

Syntax

function ibec_GetGlobalVar(VarName : string; DefaultValue : variant) :variant;

Example

The following example illustrates the use of this function, together with ibec_SetGlobalVar, described within an SQL script:

```
CONNECT ...;

execute ibeblock
as
begin
  select myfield from mytable
  where something = 25
  into :MyVar;
  ibec_SetGlobalVar('MyGlobalVar', MyVar);
end;

...

execute ibeblock
as
begin
  MyVar = ibec_GetGlobalVar('MyGlobalVar', null);
  if (MyVar = 1) then
    insert into mytable ...;
  else if (MyVar = 2) then
    update mytable set ...;
end;
```

It is also possible to specify global VAR values for IBEBlocks using the command line:

1. G<variable_name>=<value>.

Or alternatively specify global VAR values using INI files. Please refer to IBEScript for details and examples.

From:
https://ibexpert.com/docu/ - **IBExpert**

Permanent link:
https://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec_getglobalvar

Last update: **2023/07/05 19:01**