

# ibec\_GetStatementPlan

ibec\_GetStatementPlan returns the standard InterBase/Firebird plan of the specified statement.  
[ibec\\_GetStatementExplainPlan](#) returns the extended plan which is available when working with the Firebird 3 server.

## Syntax

```
function ibec_GetStatementPlan(Database : variant;
                                Statement : string;
                                RaiseError : boolean) : variant;
```

The RaiseError parameter specifies how to handle possible errors when requesting a plan. If RaiseError is equal to TRUE and an error occurs, an error will be raised and both functions will return an error message as a result. Otherwise in case of error functions it just returns an empty string.

## Example

```
execute ibeblock
as
begin
  db = ibec_GetDefaultConnection();
  sQuery = 'select * from rdb$fields where rdb$field_name = :field_name';
  sPlan = ibec_GetStatementPlan(db, sQuery, FALSE);
  sQuery = 'select * from rdb$relations where rdb$relation_name = ?';
  sPlan = ibec_GetStatementPlan(db, sQuery, FALSE);
end
```

From:  
<http://ibexpert.com/docu/> - IBExpert

Permanent link:  
[http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec\\_getstatementplan](http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec_getstatementplan)

Last update: 2023/05/22 11:12

