ibec_GetViewRecreateScript

Creates a Recreate script for a specified view(s) and returns it as a result.

Syntax

```
  function ibec_GetViewRecreateScript(Connection : variant; ViewName :
string;
  Options : string; ProgressBlock : variant) : string;
```

Connection	An active connection created with the ibec_CreateConnection function.
ViewName	List of names of view(s), delimited with semicolon or comma, for which a *Recreate* script will be created.
Options	List of options delimited with semicolon; possible options are:
GenerateCreate	Determines whether a CREATE DATABASE statement should be included at the beginning of the generated script.
GenerateConnect	Determines whether a CONNECT statement should be included at the beginning of the generated script.
IncludePassword	Determines whether the password should be included into the CREATE DATABASE or the CONNECT statement in the resulting SQL script.
SupressComments	Use to supress comments in the resulting script.
ExtractDescriptions	Determines whether database objects' descriptions should be included in the generated script. By default this option is enabled.
DescriptionsAsUpdate	Determines whether the raw UPDATE statement should be used for object descriptions instead of the IBExpert specific DESCRIBE statement.
UseComment	Generates the COMMENT ON statement for object descriptions (Firebird 2.x).
DontUseSetTerm	Don't use SET TERM statements, all statements will be separated by semicolon only.
UseCreateOrAlter	Generates CREATE OR ALTER instead of CREATE/ALTER where possible.
ProgressBlock	An IBEBlock which will be executed for every progress message generated during script execution. May be NULL or empty.

Description

ibec_GetViewRecreateScript creates a Recreate script for a specified view(s) and returns it as a result.

Use the IBExpert DB Explorer context-sensitive menu item, *Apply Block to selected objects* ... to recreate selected views based on IBEBlock and the ibec_GetViewRecreateScript function.

Example

```
  execute ibeblock
  as
  begin
    cbb = 'execute ibeblock (MsgData variant)
```

```
            as
            begin
              ibec_Progress(MsgData);
            end';
    ...
    RecreateScript = ibec_GetViewRecreateScript(mydb, 'VIEW_A; VIEW_B;
VIEW_C',
        'GenerateConnect; IncludePassword; UseCreateOrAlter', cbb);
    Res = ibec_ExecSQLScript(null, RecreateScript, 'ServerVersion=FB21',
cbb);
  end
```

From:
https://www.ibexpert.com/docu/ - **IBExpert**

Permanent link:
https://www.ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec_getviewrecreatescript

Last update: **2023/07/05 19:04**