

ibec_SetGlobalVar

ibec_SetGlobalVar allows you to create/modify a global [variable](#). This function always returns 0.

Syntax

```
function ibec_SetGlobalVar(VarName : string; VarValue : variant):variant;
```

Description

If you're using the [ibec_SetGlobalVar](#) function within scripts executed with [IBEScript](#), it is not necessary to free global variables - they will be destroyed automatically after the script has finished.

If you're using the [ibec_SetGlobalVar](#) function within IBExpert ([SQL Editor](#) or the [Script Executive](#)), any global variables created will continue to exist until you close IBExpert. So if necessary, you should free them manually using the [ibec_FreeGlobalVar](#) function.

Example

The following example illustrates the use of this function, together with [ibec_GetGlobalVar](#), described within an SQL script:

```
CONNECT ...;

execute ibeblock
as
begin
    select myfield from mytable
    where something = 25
    into :MyVar;
    ibec_SetGlobalVar('MyGlobalVar', MyVar);
end;

...
execute ibeblock
as
begin
    MyVar = ibec_GetGlobalVar('MyGlobalVar', null);
    if (MyVar = 1) then
        insert into mytable ...;
    else if (MyVar = 2) then
        update mytable set ...;
end;
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec_setglobalvarle

Last update: **2023/07/05 19:34**

