ibec_SetGlobalVar

ibec_SetGlobalVar allows you to create/modify a global variable. This function always returns 0.

Syntax

```
function ibec_SetGlobarVar(VarName : string; VarValue : variant):variant;
```

Description

If you're using the ibec_SetGlobalVar function within scripts executed with IBEScript, it is not necessary to free global variables - they will be destroyed automatically after the script has finished.

If you're using the ibec_SetGlobalVar function within IBExpert (SQL Editor or the Script Executive), any global variables created will continue to exist until you close IBExpert. So if necessary, you should free them manually using the ibec_FreeGlobalVar function.

Example

The following example illustrates the use of this function, together with ibec_GetGlobalVar, described within an SQL script:

```
CONNECT ...;

execute ibeblock
as
begin
  select myfield from mytable
  where something = 25
  into :MyVar;
  ibec_SetGlobalVar('MyGlobalVar', MyVar);
end;

...

execute ibeblock
as
begin
  MyVar = ibec_GetGlobalVar('MyGlobalVar', null);
  if (MyVar = 1) then
    insert into mytable ...;
  else if (MyVar = 2) then
    update mytable set ...;
end;
```

From:
https://www.ibexpert.com/docu/ - **IBExpert**

Permanent link:
https://www.ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-27-miscellaneous-functions:ibec_setglobalvarle

Last update: **2023/07/05 19:34**