

RunMe.ibeblock

```
execute ibeblock ExtractMetadata (  
    CodeDir varchar(1000) = 'E:\IBEBlocks\' comment 'Path to necessary  
IBEBlocks'  
    ScriptFile varchar(1000) = 'E:\BlockScript.sql' comment 'Name of the  
script file')  
returns (TimeAll float)  
as  
begin  
    Time1 = [[ibec_GetTickCount()]];  
    SPExtr = [[ibec_LoadFromFile]](CodeDir || '[[Extract-SPExtractIBEBlock |  
SPExtract.ibeblock]]');  
    DomExtract = ibec_LoadFromFile(CodeDir || '[[Extract-DomExtractIBEBlock |  
DomExtract.ibeblock]]');  
    GensExtract = ibec_LoadFromFile(CodeDir || '[[Extract-GensExtractIBEBlock  
| GensExtract.ibeblock]]');  
  
    FS = [[ibec_fs_OpenFile]](ScriptFile, __fmCreate);  
    execute ibeblock DomExtract (FS);  
    execute ibeblock GensExtract (1, FS);  
    execute ibeblock SPExtr (CodeDir, 'CREATE', 3, TRUE, FS);  
    execute ibeblock SPExtr (CodeDir, 'ALTER', 3, FALSE, FS);  
    [[ibec_fs_CloseFile]](FS);  
    Time2 = ibec_GetTickCount();  
    TimeAll = (Time2 - Time1) / 1000;  
    suspend;  
end
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
<http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:extract-metadata-using-ibeblock:runme>

Last update: **2023/05/26 17:37**

