

# InputForm.ibeblock

```
execute ibeblock (  
  returns (htmlpage blob)  
as  
begin  
  htmlpage = '<SCRIPT> function ShowDDL(){location.href = "TableChanged"  
this.focus()}</SCRIPT>';  
  htmlpage = htmlpage || '<P>Select a table from the list below to get its  
DLL:</P>  
          <SELECT ID="TableSelect" OnChange="ShowDDL()">';  
  for select rdb$relation_name, rdb$relation_id from rdb$relations  
    order by rdb$relation_name  
    into :rel_name, :rel_id  
  do  
  begin  
    rel_name = [[ibec_Trim]](rel_name);  
    htmlpage = htmlpage || [[ibec_chr]](13) || ibec_chr(10) || ' <option  
value="" || :rel_id || '>' || rel_name || '</OPTION>';  
  end  
  htmlpage = htmlpage || ibec_chr(13) || ibec_chr(10) || '</SELECT>';  
  htmlpage = htmlpage || '<P></P><P ID="FAKE">';  
end
```

From:

<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:

<http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:ibeblock-user-forms:inputform>

Last update: **2023/05/26 18:36**

