

# ftp\_download\_file

```
execute ibeblock(  
  HostName variant,  
  UserName variant,  
  Pwd variant,  
  RemoteDir variant = '\',  
  RemoteFileName variant,  
  DownloadFileName variant,  
  ShowLog boolean = TRUE)  
as  
begin  
  ftp = ibec_ftp_OpenSession('');  
  try  
    ibec_ftp_SetProperty(ftp, 'HostName', HostName);  
    ibec_ftp_SetProperty(ftp, 'UserName', UserName);  
    ibec_ftp_SetProperty(ftp, 'Password', Pwd);  
  
    --ibec_ftp_SetProperty(ftp, 'PassiveMode', FALSE);  
    --ibec_ftp_SetProperty(ftp, 'TransferMode', 'ASCII');  
  
    Res = ibec_ftp_Connect(ftp);  
  
    if (Res) then  
      begin  
        ibec_ftp_ChangeDir(ftp, RemoteDir);  
        Res = ibec_ftp_GetFile(ftp, RemoteFileName, DownloadFileName);  
        if (Res) then  
          ibec_ShowMessage('Success!');  
        end  
  
        if (ShowLog) then  
          ibec_ShowMessage(ibec_ftp_GetProperty(ftp, 'SESSIONLOG'));  
      finally  
        ibec_ftp_CloseSession(ftp);  
      end;  
    end;  
end;
```

From:  
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:  
[http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:ibec\\_ftp:ftp\\_download\\_file](http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:ibec_ftp:ftp_download_file)

Last update: **2023/05/27 08:02**

