

ftp_folders

```
execute ibeblock(
  HostName variant,
  UserName variant,
  Pwd variant,
  RemoteDir variant = '\')
as
begin
  FTPSession = ibec_ftp_OpenSession('');
  try
    ibec_ftp_SetProperty(FTPSession, 'HostName', HostName);
    ibec_ftp_SetProperty(FTPSession, 'UserName', UserName);
    ibec_ftp_SetProperty(FTPSession, 'Password', Pwd);

    --ibec_ftp_SetProperty(FTPSession, 'PassiveMode', FALSE);
    --ibec_ftp_SetProperty(FTPSession, 'TransferMode', 'ASCII');

    Res = ibec_ftp_Connect(FTPSession);

    if (Res) then
      begin
        if (ibec_ftp_ChangeDir(FTPSession, RemoteDir)) then
          ibec_ftp_MakeDir(FTPSession, 'DataFiles');
          ibec_ShowMessage(ibec_ftp_LastResponse(FTPSession));
        if (ibec_ftp_Rename(FTPSession, 'db.fdb', 'old_db.fdb')) then
          ibec_ShowMessage(ibec_ftp_LastResponse(FTPSession));
        ibec_ftp_RemoveDir(FTPSession, 'DataFiles');
        ibec_ShowMessage(ibec_ftp_LastResponse(FTPSession));

      end

    finally
      ibec_ftp_CloseSession(FTPSession);
    end;
  end;
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:ibec_ftp:ftp_folders

Last update: **2023/05/27 08:06**

