

F_LINEWRAP

compatibility to FreeUDFLib, FreeUDFLibC, FreeUDFLib AvERP, GrUDF

Entrypoint linewrap **not compatible with UTF-8 - use U_LINEWRAP**

U_LINEWRAP

function from adhoc

Entrypoint u_linewrap **compatible with UTF-8**

Inputs/Outputs

Input	CSTRING(32760)	String
	INTEGER	starting position
	INTEGER	measure
Output	CSTRING(32760)	Spends all words of the string, begin with the initial position, which are all not longer than the measure.

Syntax

```

Counting starts with 0.
TestSQL
SELECT  'alle einer Geburtstagsparty' AS ISCORRECT, F_LINEWRAP('Wir gehen
alle einer Geburtstagsparty', 10, 30)
FROM RDB$DATABASE;
SELECT  'alle einer' AS ISCORRECT, F_LINEWRAP('Wir gehen alle einer
Geburtstagsparty', 10, 29) FROM
RDB$DATABASE;
SELECT  NULL AS ISCORRECT, F_LINEWRAP(NULL, NULL, NULL) FROM
RDB$DATABASE;

```

From:
<http://ibexpert.com/docu/> - IBExpert

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-01-string-functions:04-01-02-edit-functions:f_linewrap-u_linewrap

Last update: 2023/04/04 20:26

