

F_REPLACE(F_REPLACE4, F_REPLACE8), F_BIGREPLACE

compatibility to FreeUDFLibC

Entrypoint replace **compatible with UTF-8**

Inputs/Outputs

Input exchanged	CSTRING(32760)	string where a character string had to be
	CSTRING(254)	old string
	CSTRING(254)	new string
Output parameter 2 with characters	CSTRING(32760)	string with replaced characters from
		from parameter 3

Syntax

Easy version of the funktion F_REPLACESTRING without the possibility to change the string more than one time and independent of upper and lower case.

TestSQL

```
SELECT 'Dies ist ein Versuch zwei Versuch drei Versuch vier TEST' AS  
ISCORRECT, F_REPLACE('Dies ist ein Test zwei Test  
drei Test vier TEST', 'Test', 'Versuch') FROM RDB$DATABASE;  
SELECT NULL AS ISCORRECT, F_REPLACE(NULL, NULL, NULL) FROM RDB$DATABASE;
```

From:
<http://ibexpert.com/docu/> - IBExpert

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-01-string-functions:04-01-02-edit-functions:f_replace-f_bigreplace

Last update: 2023/04/04 21:12

