

F_RIGHT(F_RIGHT4, F_RIGHT8), F_BIGHRIGHT

compatibility to FreeUDFLib, FreeUDFLibC, FreeUDFLib AvERP, GrUDF

Entrypoint right **not compatible with UTF-8** - use U_RIGHT(U_RIGHT4, U_RIGHT8)

U_RIGHT(U_RIGHT4, U_RIGHT8)

function from adhoc

Entrypoint u_right **compatible with UTF-8**

Inputs/Outputs

Input	CSTRING(254)	String
	INTEGER	length of the cut-off-string
Output	CSTRING(254)	string cut on the number indication from
right gives from parameter 2		

Syntax

```
Counting starts with 1
TestSQL
SELECT 'n Test' AS ISCORRECT, F_RIGHT('Dies ist ein Test', 6) FROM
RDB$DATABASE;
SELECT NULL AS ISCORRECT, F_RIGHT(NULL, NULL) FROM RDB$DATABASE;
```

From:
<http://ibexpert.com/docu/> - IBExpert

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-01-string-functions:04-01-02-edit-functions:f_right-f_bighright-u_right

Last update: 2023/04/04 21:30

