

F_BLOBSTRPOS

input/output-compatibility to rFunc (B_STRPOS)

Entrypoint b_strpos **not compatible with UTF-8 - if needed please ask**

Inputs/Outputs

Input	CSTRING(8190) BLOB	String to search in BLOB BLOB in which is to search
Output	INTEGER	starting-position of the string in BLOB, 0 if not found

Syntax

case/uppercase for search-string is important. Counting for starting-position starts at 1.

TestSQL (for TestISO.GDB/FDB)

```
SELECT 5 AS ISCORRECT, F_BLOBSTRPOS('zwei', TEXTBLOB) FROM BLOBTEST WHERE  
BLOBTESTID = 2;
```

```
SELECT 0 AS ISCORRECT, F_BLOBSTRPOS('Zwei', TEXTBLOB) FROM BLOBTEST WHERE  
BLOBTESTID = 2;
```

```
SELECT NULL AS ISCORRECT, F_BLOBSTRPOS(NULL, NULL) FROM BLOBTEST WHERE  
BLOBTESTID = 2;
```

From:

<http://ibexpert.com/docu/> - IBExpert

Permanent link:

http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-04-blob-functions:04-04-05-find_determine:f_blobstrpos

Last update: 2023/04/16 19:30

