

F_UUID2UUIDCOMPR

return-compatible to function GUID_TO_UUID in uuidlib

Entrypoint uuid2uuidcompr compatible with UTF-8

Inputs/Outputs

Input	CSTRING(250)	valid UUID every version
Output	CSTRING(22)	compressed UUID

Syntax

TestSQL (to use with TestISO.GDB)

If you take a compressed UUID for input instead of a normal UUID:

```
SELECT UUIDTESTID, 'Input no RFC4122 UUID' AS ISCORRECT,  
F_UUID2UUIDCOMPR(UUIDCOMPR) FROM UUIDTEST WHERE UUIDCOMPR IS NOT NULL ORDER  
BY 1;
```

If you take a normal string for input instead of a normal UUID:

```
SELECT 'Input no RFC4122 UUID' AS ISCORRECT, F_UUID2UUIDCOMPR('abcde')  
FROM RDB$DATABASE;
```

If you take a normal UUID for input (right):

```
SELECT UUIDTESTID, UUIDCOMPR AS ISCORRECT, F_UUID2UUIDCOMPR(UUID) FROM  
UUIDTEST WHERE UUIDCOMPR IS NOT NULL ORDER BY 1;  
SELECT NULL AS ISCORRECT, F_UUID2UUIDCOMPR(NULL) FROM RDB$DATABASE;
```

From:

<http://ibexpert.com/docu/> - IBExpert

Permanent link:

http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-05-uuid-functions:04-05-02-transform:f_uuid2uuidcompr

Last update: 2023/04/16 19:46

