

F_UUID1MACCOMPRMAC

function from adhoc

Entrypoint uuid1maccomprmac **compatible with UTF-8**

Inputs/Outputs

Input	CSTRING(250)	valid compressed UUID version 1a
Output	CSTRING(17)	MAC-address of the computer where UUID was created

Syntax

```
TestSQL (to use with TestISO.GDB)
If you take a normal UUID for input instead of a compressed UUID:
SELECT UUIDTESTID, F_UUIDVERSION(UUID), ART, NULL AS ISCORRECT,
F_UUID1MACCOMPRMAC(UUID) FROM UUIDTEST ORDER BY 1;
If you take a compressed UUID for input (right):
SELECT UUIDTESTID, F_UUIDVERSION(UUID), ART, MACADDRESS AS ISCORRECT,
F_UUID1MACCOMPRMAC(UUIDCOMPR) FROM UUIDTEST ORDER BY 1;
SELECT NULL AS ISCORRECT, F_UUID1MACCOMPRMAC(NULL) FROM RDB$DATABASE;
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-05-uuid-functions:04-05-03-read:f_uuid1maccomprmac

Last update: **2023/04/16 19:51**

