

F_UUIDVERSION

function from adhoc

Entrypoint uuidversion compatible with UTF-8

Inputs/Outputs

Input	CSTRING(250)	valid UUID
Output	CSTRING(20)	(variant and) version of the UUID

Syntax

```
Possible variants are: (not yet implemented)
    0    NCS (reserved for backwards compatibility)
    10   the actual variant as described in the RFC4122
    110  Microsoft (reserved for backward-compatibility)
    111  reserved for further variants
Possible versions are:
    1    time-based
        a. with a real MAC-address described in the IEEE 802-standard
        b. with a random-generated MAC-Address described in the IEEE 802-
standard
    2    DCE-security-version (with POSIX UUIDs)
    3    namespace-based (with MD5)
    4    random created
    5    namespace-based (SHA-1)
The function returns:
    V1a
    V1b
    V3
        V4
    V5
TestSQL (für TestISO.GDB)
SELECT ART, F_UUIDVERSION(UUID) FROM UUIDTEST ORDER BY UUIDTESTID;
SELECT NULL AS ISCORRECT, F_UUIDVERSION(NULL) FROM RDB$DATABASE;
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-05-uuid-functions:04-05-03-read:f_uuidversion

Last update: **2023/04/16 19:57**

