

F_IF

function from adhoc

Entrypoint aif **compatible with UTF-8**

Inputs/Outputs

Input	CSTRING(32)	Comparisonstring 1
	CSTRING(8)	Comparisonoperator
	CSTRING(32)	Comparisonstring 2
	CSTRING(8190)	if comparison applies, then result =
Parameter 4		
	CSTRING(8190)	if comparison does not apply, then result =
Parameter 5		
Output	CSTRING(8190)	s.o.

Syntax

"reproduction" of a IF-loop
Comparisonoperator

```
=
<>
<
>
<=
>=
```

Everyone of these operators a "n" (numeric) can be placed in front, if the two compared strings contain floatingpoint, e.g. n =

TestSQL

```
SELECT 'Parameter 1 ist kleiner' AS ISCORRECT, F_IF('Test', '<=',
'Testa', 'Parameter 1 ist kleiner', 'Parameter 1 ist größer') FROM
RDB$DATABASE;
```

```
SELECT 'Parameter 1 ist größer' AS ISCORRECT, F_IF('Testb', '<=',
'Testa', 'Parameter 1 ist kleiner', 'Parameter 1 ist größer') FROM
RDB$DATABASE;
```

```
SELECT 'Parameter 1 ist kleiner' AS ISCORRECT, F_IF('Test1', 'n<=',
'Test2', 'Parameter 1 ist kleiner', 'Parameter 1 ist größer') FROM
RDB$DATABASE;
```

```
SELECT 'Parameter 1 ist kleiner' AS ISCORRECT, F_IF('123.45', 'n<=',
'234.56', 'Parameter 1 ist kleiner', 'Parameter 1 ist größer') FROM
RDB$DATABASE;
```

```
SELECT NULL AS ISCORRECT, F_IF(NULL, NULL, NULL, NULL, NULL) FROM
```

RDB\$DATABASE ;

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
http://ibexpert.com/docu/doku.php?id=04-ibexpert-udf-functions:04-09-divers-functions:04-09-01-diverse-functions:f_if

Last update: **2023/04/18 17:02**

