

ibec_ibe_SetDatabaseProp

The ibec_ibe_SetDatabaseProp function sets the value of specified database property.

All ibec_ibe_xxx functions work only within IBExpert and will be ignored when IBEBlock is executed with IBEScript.exe or IBEScript.dll.

Description

No additional description...

Syntax

The ibec_ibe_SetDatabaseProp function sets the value of specified database property.

All ibec_ibe_xxx functions work only within IBExpert and will be ignored when IBEBlock is executed with IBEScript.exe or IBEScript.dll.

ALIAS	Alias of the registered database.
CLIENTLIB	Name of the client library file specified in the database registration info .
SERVERNAME or HOSTNAME	Server name.
FILENAME or DBNAME	Database file name.
PASSWORD	Password specified in the database registration info.
USERNAME or USER_NAME or USER	User name.
ROLENAME or ROLE_NAME or ROLE	Role name.
NAMES or LC_CTYPE or CHARSET	Connection charset .
CONNECTIONSTRING or CONNECTION_STRING	Connection string.
ACTIVE or CONNECTED	Returns TRUE if the database is active and FALSE if it is not.

From:
<http://ibexpert.com/docu/> - IBExpert

Permanent link:
<http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-07-database-functions-ibexpert:ibec-ibe-setdatabaseprop>

Last update: 2023/07/06 04:14

