

# ibec\_ibe\_SetLngShortcut

ibec\_ibe\_SetLngShortcut changes the shortcut of a specified IBExpert action.

## Description

No additional description...

## Syntax

```
function ibec_ibe_SetLngShortcut(StrID : integer; Value : variant) :  
variant;
```

ibec\_ibe\_SetLngShortcut changes the shortcut of a specified IBExpert action. StrID is the identifier of the language resource string associated with the action. String identifiers are listed in Tools | Localize IBExpert.

Value is an integer or string representation of the shortcut, for example 'Ctrl+Alt+F7'.

If successful, ibec\_ibe\_SetLngShortcut returns an integer value which represents the new shortcut, otherwise it returns NULL.

## Example 1

Changing the shortcut of the Disconnect from database action:

```
Res = ibec_ibe_SetLngShortcut(1019, 'Shift+Alt+D');
```

## Example 2

Clear the shortcut of the Connect to database action:

```
Res = ibec_ibe_SetLngShortcut(1018, 0);
```

From:  
<http://ibexpert.com/docu/> - IBExpert

Permanent link:  
<http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-07-database-functions-ibexpert:ibec-ibe-setlngshortcut>

Last update: 2023/05/02 17:27

