

# ibec\_msxml\_GetError

## Description

No additional description...

## Syntax

```
function ibec_msxml_GetError(xml, '');
```

## Example

```
EXECUTE IBEBLOCK
as
begin
%blue% -- Get file %%
    xmlfile = 'http://www.pwebapps.ezv.admin.ch/rates/estv/getavgxml'; %blue%-
- wrong path%%
    --xmlfile = 'http://www.pwebapps.ezv.admin.ch/apps/rates/estv/getavgxml';
%blue%-- correct path%%
    xml = ibec_msxml_Create();
    try
        res = ibec_msxml_Load(xml, xmlfile);
        if (res) then
            nodes = ibec_msxml_SelectNodes(xml, 'monatsmittelkurs/devise');
        else
            begin
                %blue% -- Get error code (default behaviour without Return option)%%
                ErrCode = ibec_msxml_GetError(xml, '');
                %blue% -- Get error message%%
                ErrMessage = ibec_msxml_GetError(xml, 'Return=Message');
                ibec_ShowMessage(ErrCode || ' : ' || ErrMessage);
            end
        finally
            ibec_msxml_Free(xml);
        end;
    end
end
```

From:  
<http://ibexpert.com/docu/> - IBExpert

Permanent link:  
[http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-09-working-with-xml-data:ibec\\_msxml\\_geterror](http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-09-working-with-xml-data:ibec_msxml_geterror)

Last update: 2023/05/04 16:24

