

# ibec\_ftp\_GetProperty

## Description

ibec\_ftp\_GetProperty gets the value of the specified property.

## Syntax

```
function ibec_ftp_GetProperty(FTPSession : variant; PropertyName : string)
: variant;
```

ibec\_ftp\_GetProperty returns the value of the specified property of the FTP server object. PropertyName is a name of the property to read. If the property name is unknown the function will return NULL.

## Example

The following properties are available for reading:

<b>Host (or HostName)</b>	<b>returns the URL of the FTP server name.</b>
User (or UserName)	returns the user name.
Pass (or Password)	returns the password.
Port	returns the port number (as a string).
Data	returns the content of the internal data buffer.
SessionLog	returns the session log data.
LastResponse	returns the last response of the FTP server (same as <a href="#">ibec_ftp_LastResponse</a> ).

## Examples

- [ibec\\_ftp\\_GetFile: Example 2](#)
- [ibec\\_ftp\\_SetProperty](#)

From:  
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:  
[http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-16-ftp-server-functions:ibec\\_ftp\\_getproperty](http://ibexpert.com/docu/doku.php?id=05-ibexpert-ibeblock-functions:05-16-ftp-server-functions:ibec_ftp_getproperty)

Last update: **2023/07/06 15:45**

