

Automatic database structure comparison with recompilation of triggers and procedures

```
execute ibeblock
as
begin
    create connection MasterDB dbname 'localhost:c:\db1.fdb'
    password 'masterkey' user 'SYSDBA'
    clientlib 'fbclient.dll';

    create connection SubscriberDB dbname 'localhost:c:\db2.fdb'
    password 'masterkey' user 'SYSDBA'
    clientlib 'fbclient.dll';

    cbb = 'execute ibeblock (LogMessage variant)
        as
        begin
            ibec_progress(LogMessage);
        end';
    ibec_CompareMetadata(MasterDB, SubscriberDB, 'E:\CompRes.sql',
'OmitDescriptions; OmitGrants', cbb);

    close connection MasterDB;
    close connection SubscriberDB;
end ;

input 'E:\CompRes.sql';

execute ibeblock
as
begin
    create connection SubscriberDB dbname 'localhost:c:\db2.fdb'
    password 'masterkey' user 'SYSDBA'
    clientlib 'fbclient.dll';

    e=ibec_RecompileProcedure(SubscriberDB, '');
    e=ibec_RecompileTrigger(SubscriberDB, '')
    close connection SubscriberDB;
end;
```

From:
<http://ibexpert.com/docu/> - IBExpert

Permanent link:
<http://ibexpert.com/docu/doku.php?id=06-ibexpert-ibeblock-examples:automatic-database-structure-comparison-with-recompilation-of-triggers-and-procedures>

Last update: 2023/05/26 17:48

