

DROP DATABASE

Please note that this function is deprecated. Please use [ibec_DropDatabase](#) instead.

Deletes a specified database.

Syntax

```
DROP DATABASE 'filespec' USER 'username' PASSWORD 'password'  
[CLIENTLIB 'libfile'];
```

Argument	Description
'filespec'	A database file specification; file naming conventions are platform-specific.
USER 'username'	Checks the username against valid user name and password combinations in the security database (Server security ISC4.GDB / SECURITY.FDB) on the server where the database will reside.
PASSWORD 'password'	Checks the password against valid user name and password combinations in the security database on the server where the database will reside; can be up to 8 characters.
CLIENTLIB 'libfile'	Client library file name; default: gds32.dll.

Description

DROP DATABASE deletes specified database, including any associated secondary, shadow, and log files. Dropping a database deletes any data it contains.

A database can be dropped by its creator, the SYSDBA user, and any users with operating system root privileges.

Example

```
execute ibeblock  
as  
begin  
    drop database 'localhost/3060:c:\db1.fdb' user 'SYSDBA' password  
    'masterkey'  
    clientlib 'C:\Program Files\Firebird\bin\fbclient.dll';  
end
```

From:
<http://ibexpert.com/docu/> - **IBExpert**

Permanent link:
<http://ibexpert.com/docu/doku.php?id=07-procedural-extensions-of-ibeblock:drop-database>

Last update: **2023/05/27 08:57**

